

Specifications	Acrylic based glue			Printing one side only			Finishing one side only			Usage		Condition		
Materials	Permanent	Removable	Permanent water resistant	CMYK	CMYK + White	Black only	Gloss varnish	Gloss lamination	Matt lamination	Humidity resistant	Food contact	Indirect UV resistance	Temperature min / max	Storage
PP gloss white	✓						✓	✓	✓	✓	Indirect	6 months	-20°C / +80°C	1 year at 22°C
PP gloss transparent	✓				✓		✓	✓	✓	✓	Indirect	6 months	-20°C / +80°C	6 months at 22°C
PP gloss metallic	✓				✓		✓	✓	✓		Indirect	6 months	-20°C / +80°C	2 years at 22°C
Gloss coated	✓						✓	✓	✓		Indirect	6 months	-10°C / +65°C	2 years at 22°C
Gloss coated		✓		✓			✓	✓	✓		Indirect	6 months	5°C / +60°C	2 years at 22°C
Fluorescent yellow	✓					✓					Indirect	6 months	-20°C / +80°C	2 years at 22°C
Uncoated paper			✓	✓							Indirect	6 months	-10°C / +75°C	1 year at 22°C
Embossed pearlescent paper			✓	✓			✓				Indirect	6 months	-10°C / +75°C	2 years at 22°C